

Model	T101-20CL 84	T101-22CL 84	T101-24CL 84	T101-26CL 84	T101-28CL 84	T101-30CL 84	T101-32CL 84
Overall Length	24'-7"	26'-7"	28'-7"	30'-7"	32'-7"	34'-7"	36'-7"
Overall Width	102"	102"	102"	102"	102"	102"	102"
Overall Height	109"	109"	109"	109"	109"	109"	109"
Interior Length	20'-9"	22'-9"	24'-9"	26'-9"	28'-9"	30'-9"	32'-9"
Interior Width	98 1/2"	98 1/2"	98 1/2"	98 1/2"	98 1/2"	98 1/2"	98 1/2"
Between Wheel Wells	82"	82"	82"	82"	82"	82"	82"
Interior Height	82"	82"	82"	82"	82"	82"	82"
Deck Height	24"	24"	24"	24"	24"	24"	24"
*Empty Weight (lbs)	3900	4100	4300	4450	4755	4870	5020
*Gross Capacity (GVWR)	9990	9990	9990	9990	9990	9990	9990
*Payload Capacity (lbs)	6090	5890	5690	5540	5235	5120	4970
Tongue Construction	6" tube	6" tube	6" tube	6" tube	6" tube	6" tube	6" tube
Tongue Length	3'-5"	3'-5"	3'-5"	3'-5"	3'-5"	3'-5"	3'-5"
Coupler	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame
Coupler Height	23"	23"	23"	23"	23"	23"	23"
Jack	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg
Crossmember Spacing	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Wall Uprights Spacing	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Roof Bow Spacing	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Exterior Sheeting	.040	.040	.040	.040	.040	.040	.040
Side Escape Door	yes	yes	yes	yes	yes	yes	yes
Side Escape Door Height	68"	68"	68"	68"	68"	68"	68"
Side Escape Door Width	36"	36"	36"	36"	36"	36"	36"
Rear Door Type	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp
Rear Door Opening Height	78"	78"	78"	78"	78"	78"	78"
Rear Door Opening Width	95"	95"	95"	95"	95"	95"	95"
Ramp Load Capacity (lbs)	4000	4000	4000	4000	4000	4000	4000
Axles (lbs)	(2) 5200	(2) 5200	(2) 5200	(2) 5200	(2) 5200	(2) 5200	(2) 5200
Axle Type	Torsion brake	Torsion brake	Torsion brake	Torsion brake	Torsion brake	Torsion brake	Torsion brake
Brakes	yes	yes	yes	yes	yes	yes	yes
Breakaway Kit with Battery	yes	yes	yes	yes	yes	yes	yes
Tire Size	ST225/75	ST225/75	ST225/75	ST225/75	ST225/75	ST225/75	ST225/75
Tire Load Range	D	D	D	D	D	D	D
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	6 on 5.5	6 on 5.5	6 on 5.5	6 on 5.5	6 on 5.5	6 on 5.5	6 on 5.5
Brake Lights	LED	LED	LED	LED	LED	LED	LED
Clearance/Marker Lights	LED	LED	LED	LED	LED	LED	LED
Trailer Plug	7-way	7-way	7-way	7-way	7-way	7-way	7-way
Gooseneck Option							
Overall Length	28'-4"	30'-4"	32'-4"	34'-4"	36'-4"	38'-4"	38'-4"
Interior Length	19'-6"	21'-6"	23'-6"	25'-6"	27'-6"	29'-6"	29'-6"
Gooseneck Interior Length	7'	7'	7'	7'	7'	7'	7'
*Empty Weight (lbs)	4900	5100	5330	5450	5755	5870	5870
*Gross Capacity (GVWR)	9990	9990	9990	9990	9990	9990	9990
*Payload Capacity (lbs)	5090	4890	4660	4540	4235	4120	4120