Model	T101.20CR 72	T101.22CR 72	T101.24CR 72	T101.26CR 72	T101.28CR 72	T101.30CR 72	T101.32CR 72
Overall Length	24'-7"	26'-7"	28'-7"	30'-7"	32'-7"	34'-7"	36'-7"
Overall Width	102"	102"	102"	102"	102"	102"	102"
Overall Height	106"	106"	106"	106"	106"	106"	106"
Interior Length	20'-9"	22'-9"	24'-9"	26'-9"	28'-9"	30'-9"	32'-9"
Interior Width	98 1/2"	98 1/2"	98 1/2"	98 1/2"	98 1/2"	98 1/2"	98 1/2"
Between Wheel Wells	82"	82"	82"	82"	82"	82"	82"
Interior Height	83"	83"	83"	83"	83"	83"	83"
Deck Height	24"	24"	24"	24"	24"	24"	24"
*Empty Weight (lbs)	3310	3580	3890	4125	4350	4665	4980
*Gross Capacity (GVWR)	9990	9990	9990	9990	9990	9990	9990
*Payload Capacity (lbs)	6680	6410	6100	5865	5640	5325	5010
Tongue Construction	6" tube	6" tube	6" tube	6" tube	6" tube	6" tube	6" tube
Tongue Length	3'-5"	3'-5"	3'-5"	3'-5"	3'-5"	3'-5"	3'-5"
Coupler	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame
Coupler Height	23"	23"	23"	23"	23"	23"	23"
Jack	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg
Crossmember Spacing	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Wall Uprights Spacing	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Roof Bow Spacing	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Exterior Sheeting	.040	.040	.040	.040	.040	.040	.040
Side Escape Door	yes	yes	yes	yes	yes	yes	yes
Side Escape Door Height	68"	68"	68"	68"	68"	68"	68"
Side Escape Door Width	36"	36"	36"	36"	36"	36"	36"
Rear Door Type	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp
Rear Door Opening Height	76 1/2"	76 1/2"	76 1/2"	76 1/2"	76 1/2"	76 1/2"	76 1/2"
Rear Door Opening Width	95"	95"	95"	95"	95"	95"	95"
Ramp Load Capacity (lbs)	4000	4000	4000	4000	4000	4000	4000
Axles (lbs)	(2) 5200	(2) 5200	(2) 5200	(2) 5200	(2) 5200	(2) 5200	(2) 5200
Axle Type	Torsion brake	Torsion brake	Torsion brake	Torsion brake	Torsion brake	Torsion brake	Torsion brake
Brakes	yes	yes	yes	yes	yes	yes	yes
Breakaway Kit with Battery	yes	yes	yes	yes	yes	yes	yes
Tire Size	ST225/75	ST225/75	ST225/75	ST225/75	ST225/75	ST225/75	ST225/75
Tire Load Range	D	D	D	D	D	D	D
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	6 on 5.5	6 on 5.5	6 on 5.5	6 on 5.5	6 on 5.5	6 on 5.5	6 on 5.5
Brake Lights	LED	LED	LED	LED	LED	LED	LED
Clearance/Marker Lights	LED	LED	LED	LED	LED	LED	LED
Trailer Plug	7-way	7-way	7-way	7-way	7-way	7-way	7-way
Gooseneck Option							
Overall Length	28'-4"	30'-4"	32'-4"	34'-4"	36'-4"	38'-4"	38'-4"
Interior Length	19'-6"	21'-6"	23'-6"	25'-6"	27'-6"	29'-6"	29'-6"
Gooseneck Interior Length	7'	7'	7'	7'	7'	7'	7'
*Empty Weight (lbs)	4310	4580	4890	5125	5350	5665	5980
*Gross Capacity (GVWR)	9990	9990	9990	9990	9990	9990	9990
*Payload Capacity (lbs)	5680	5410	5100	4865	4640	4325	4010