## *H&H CA Series Round-top Single Axle Trailer Model Specifications*

| Model | SCA 4.6.48 | SCA 4.8.48 | SCA 5.8.54 | SCA 5.10.60 | SCA 6.10.66 | SCA 6.12.66 | SCA 6.14.66 | SCA 7.10.66 | SCA 7.12.66 |
|---|---|---|---|---|---|---|---|---|---|
| Overall Length | 9'-11" | 12'-0" | 12'-0" | 14'-0" | 14' 3" | 16'-1" | 17'-10" | 14'-0" | 16'-1" |
| Overall Width | 64" | 64" | 82" | 82" | 93" | 93" | 93" | 102" | 102" |
| Overall Height | 6'-6" | 6'-6" | 6'-9" | 7'-5" | 7'-11" | 7'-11" | 7'-11" | 7'-11" | 7'-11" |
| Interior Length | 6'-8" | 8'-8" | 8'-7" | 10'-8" | 10'-8" | 12'-9" | 14'-9" | 10'-9" | 12'-9" |
| Interior Width | 42" | 42" | 60" | 60" | 69" | 69" | 69" | 81 1/2" | 81 1/2" |
| Between Wheel Wells | - | - | - | - | - | - | - | - | - |
| Interior Height | 56" | 56" | 62" | 69" | 76" | 76" | 76" | 76" | 76" |
| Deck Length | 6'-9" | 7'-9" | 7'-10" | 9'-10" | 9'-10" | 11'-10" | 13'-10" | 9'-10" | 11'-10" |
| *Empty Weight (lbs) | 650 | 750 | 910 | 1130 | 1250 | 1350 | 1450 | 1400 | 1500 |
| *Gross Capacity (GVWR) | 2000 | 2000 | 2000 | 2000 | 2990 | 2990 | 2990 | 2990 | 2990 |
| *Payload Capacity (lbs) | 1350 | 1250 | 1090 | 870 | 1740 | 1640 | 1540 | 1590 | 1490 |
| Tongue Construction | 3" tube | 3" tube | 3" tube | 3" tube | 3" tube | 3" tube | 3" tube | 3" tube | 4" tube |
| Tongue Length | 37" | 37" | 39 1/2" | 39 1/2" | 39 1/2" | 39 1/2" | 39 1/2" | 42 1/2" | 42 1/2" |
| Coupler | a-frame | a-frame | a-frame | a-frame | a-frame | a-frame | a-frame | a-frame | a-frame |
| Coupler Height | 18 3/4" | 18 3/4" | 18 3/4" | 18 3/4" | 18 3/4" | 18 3/4" | 18 3/4" | 17 1/4" | 17 1/4" |
| Jack | 2K swivel | 2K swivel | 2K swivel | 2K swivel | 2K swivel | 2K swivel | 2K swivel | 2K swivel | 2K swivel |
| Crossmember Spacing | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC |
| Wall Uprights Spacing | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC |
| Roof Bow Spacing | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC | 24" OC |
| Exterior Sheeting | .024 | .024 | .024 | .024 | .024 | .024 | .024 | .024 | .024 |
| Side Escape Door | - | - | - | yes | yes | yes | yes | yes | yes |
| Side Escape Door Height | - | - | - | 56" | 62" | 62" | 62" | 62" | 62" |
| Side Escape Door Width | - | - | - | 32" | 32" | 32" | 32" | 32" | 32" |
| Rear Door Type | Side Swing | Side Swing | Side Swing | Ramp | Ramp | Ramp | Ramp | Ramp | Ramp |
| Rear Door Opening Height | 50" | 50" | 54" | 62" | 68" | 68" | 68" | 68" | 68" |
| Rear Door Opening Width | 37" | 37" | 55" | 55" | 66" | 66" | 66" | 78" | 78" |
| Ramp Load Capacity (lbs) | - | - | - | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 |
| Axles (lbs) | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 |
| Axle Type | Drop spring idler | Drop spring idler | Drop spring idler | Drop spring idler | Drop spring idler | Drop spring idler | Drop spring idler | Drop spring idler | Drop spring idler |
| Brakes | - | - | - | - | - | - | - | - | - |
| Breakaway Kit with Battery | - | - | - | - | - | - | - | - | - |
| Tire Size | ST205/75 | ST205/75 | ST205/75 | ST205/75 | ST205/75 | ST205/75 | ST205/75 | ST205/75 | ST205/75 |
| Tire Load Range | C | C | C | C | C | C | C | C | C |
| Tire Ply | Radial | Radial | Radial | Radial | Radial | Radial | Radial | Radial | Radial |
| Rim Size | 15" | 15" | 15" | 15" | 15" | 15" | 15" | 15" | 15" |
| Bolt Pattern | 5 on 4.5 | 5 on 4.5 | 5 on 4.5 | 5 on 4.5 | 5 on 4.5 | 5 on 4.5 | 5 on 4.5 | 5 on 4.5 | 5 on 4.5 |
| Brake Lights | LED | LED | LED | LED | LED | LED | LED | LED | LED |
| Clearance/Marker Lights | LED | LED | LED | LED | LED | LED | LED | LED | LED |
| Trailer Plug | 4-prong | 4-prong | 4-prong | 4-prong | 4-prong | 4-prong | 4-prong | 4-prong | 4-prong |