



Great Trailers...Great People!

SUPER SINGLE INDUSTRIAL FLATBED

tandem axle

STANDARD FEATURES

- STEEL PIERCED CHANNEL FRAME
- STEEL CHANNEL CROSSMEMBERS & TONGUE
- TREATED WOOD DECK
- OUTRIGGERS & BOARD END CAPS
- 4' SELF-CLEANING DOVETAIL
- FOLD-OVER BOBCAT RAMPS
- SPRING ASSISTED
- 1/4" DRIVE-OVER FENDERS
- 3/4" TRACTION CLEATS
- MULTIPLE STAKE POCKETS
- INVERTED CHANNEL RUB RAIL
- HEADACHE RACK
- 22500LB GVWR
- SLIPPER SPRING OIL BATH AXLES
- 4-WHEEL ELECTRIC BRAKES
- BREAKAWAY KIT & BATTERY
- DOT COMPLIANT LED LIGHTS
- SEALED WIRING HARNESS
- RADIAL SUPER SINGLE TIRES
- ADJUSTABLE HEIGHT PINTLE
- DUAL SAFETY CHAINS
- DUAL 12K DROP LEG JACKS



model shown with optional tool box

ENGINEERED & BUILT TO BE THE BEST



OPEN STEEL
MODEL

H&H TRAILERS®



Powder Coat Color Options



www.hhtrailer.com

SUPER SINGLE INDUSTRIAL FLATBED TRAILER

Model	ILSS 18+4	ILSS 20+4	ILSS 22+4	ILSS 24+4
Overall Length	26'-11"	28'-11"	30'-11"	32'-11"
Overall Width	102"	102"	102"	102"
Overall Height	36.5"	36.5"	36.5"	36.5"
Deck Height	30"	30"	30"	30"
Deck Length	18'-2"	20'-2"	22'-2"	24'-2"
Deck Width Between Fenders	83"	83"	83"	83"
Fender Height	6.5"	6.5"	6.5"	6.5"
*Curb Weight (lbs)	5375	5770	6170	6565
Gross Capacity (GVWR)	22500	22500	22500	22500
*Payload Capacity (lbs)	17125	16730	16330	15935
Tongue Construction	8" channel	8" channel	8" channel	8" channel
Tongue Length	4'-4"	4'-4"	4'-4"	4'-4"
Coupler	Adjustable height pintle	Adjustable height pintle	Adjustable height pintle	Adjustable height pintle
Coupler Height	15.5", 20", 24.5"	15.5", 20", 24.5"	15.5", 20", 24.5"	15.5", 20", 24.5"
Safety Chains & Hooks	yes	yes	yes	yes
Jack	Dual 12K	Dual 12K	Dual 12K	Dual 12K
Frame Construction	10" channel	10" channel	10" channel	10" channel
Crossmember	3" channel	3" channel	3" channel	3" channel
Ramp Length (ea)	4'-0"	4'-0"	4'-0"	4'-0"
Ramp Width (ea)	20 1/2"	20 1/2"	20 1/2"	20 1/2"
*Ramp Load Capacity (ea/lbs)	4650	4650	4650	4650
Axle (lbs)	(2) 10000	(2) 10000	(2) 10000	(2) 10000
Axle Type	Dual slipper spring	Dual slipper spring	Dual slipper spring	Dual slipper spring
Brakes	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric
Breakaway Kit w/ Battery	yes	yes	yes	yes
Tire Size	ST235/75	ST235/75	ST235/75	ST235/75
Tire Rating	H	H	H	H
Tire Ply	Radial	Radial	Radial	Radial
Rim Size	17.5"	17.5"	17.5"	17.5"
Bolt Pattern	8 on 6.5	8 on 6.5	8 on 6.5	8 on 6.5
Trailer Plug	7-prong	7-prong	7-prong	7-prong
Exterior Lighting	LED	LED	LED	LED

*All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).

Popular Options

Gooseneck Coupler
Kiln Dried Lumber
Steel Diamond Plate Deck
Super Deluxe Ramps
D-rings
Aluminum Wheels
Spare Tire & Mount
Toolbox
Winch

additional sizes & options
may be available.
ask your dealer or visit
www.hhtrailer.com
for more details.

Great Service

Top Quality

Diverse Product Lines



This brochure is for advertising purposes only. Product images and specifications are based on the latest information available at the time of publication. H&H Trailers, LLC reserves the right to make changes at any time to any models, materials, prices, specifications, and/or colors as well as discontinue models and options without notice or obligation. Photos may show optional features which are available at an additional cost. Color pallet provided may vary from actual paint colors. Please contact your AUTHORIZED DEALER for the most current information, availability, and pricing. H&H Trailers, Speed Loader, and the flame logo are the trademarks of H&H Trailers, LLC. 2012-2014 © H&H Trailers, LLC. All rights reserved.

Your Authorized H&H Dealer