	55.0860	55.7066	55.1266	56.1066	56.1266	56.1466	57.1066	57.1266	57.1466
Model	55.0	55.7	55.7	56.7	56.7	56.7	57.7	57.7	57.7
Overall Length	11'-3"	13'-3"	15'-3"	14'-4"	16'-4"	18'-4"	14'-7"	16'-7"	18'-7"
Overall Width	82"	82"	82"	92"	92"	92"	102"	102"	102"
Overall Height	7'-4"	7'-10"	7'-10"	7'-11"	7'-11"	7'-11"	8'-2"	8'-2"	8'-2"
Interior Length	8'-6"	10'-6"	12'-6"	10'-6"	12'-6"	14'-6"	10'-9"	12'-9"	14'-9"
Interior Width	59"	59"	59"	69"	69"	69"	81"	81"	81"
Between Wheel Wells	-	-	-	-	-	-	-	-	-
Interior Height	68 1/2"	74 1/2"	74 1/2"	76"	76"	76"	76"	76"	76"
Deck Height	16"	16"	16"	16"	16"	16"	20"	20"	20"
*Empty Weight (lbs)	1110	1160	1210	1320	1380	1440	1660	1740	1820
*Gross Capacity (GVWR)	2990	2990	2990	2990	2990	2990	2990	2990	2990
*Payload Capacity (lbs)	1880	1830	1780	1670	1610	1550	1330	1250	1170
Tongue Construction	3" tube	3" tube	3" tube	3" tube	3" tube	3" tube	3" tube	3" tube	3" tube
Tongue Length	1'-10"	1'-10"	1'-10"	2'-7"	2'-7"	2'-7"	3'-2"	3'-2"	3'-2"
Carrelan	2"	2"	2"	2"	2"	2"	2"	2"	2"
Coupler	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame
Coupler Height	15" 2K	15" 2K	15" 2K	15" 2K	15" 2K	15" 2K	19" 2K	19" 2K	19" 2K
Jack	swivel	swivel	swivel	swivel	swivel	swivel	swivel	swivel	swivel
	Full Tubular	Full Tubular	Full Tubular	Full Tubular	Full Tubular	Full Tubular	Full Tubular	Full Tubular	Full Tubular
Crossmember Spacing	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Wall Uprights Spacing	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Roof Bow Spacing	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Exterior Sheeting	.040	.040	.040	.040	.040	.040	.040	.040	.040
Side Escape Door	-	yes	yes	yes	yes	yes	yes	yes	yes
Side Escape Door Height	-	62"	62"	62"	62"	62"	62"	62"	62"
Side Escape Door Width	-	36"	36"	36"	36"	36"	36"	36"	36"
**Rear Door Type	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp
Rear Door Opening Height	62"	68"	68"	68"	68"	68"	68"	68"	68"
Rear Door Opening Width	56 1/2"	56 1/2"	56 1/2"	66"	66"	66"	78"	78"	78"
Ramp Load Capacity (lbs)	2000	2000	2000	2000	2000	2000	2000	2000	2000
Axles (lbs)	3500	3500	3500	3500	3500	3500	3500	3500	3500
Aula Tuna	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion
Axle Type	idler	idler	idler	idler	idler	idler	idler	idler	idler
Brakes Progkovov Kit with Botton	-	-	-	-	-	-	-	-	-
Breakaway Kit with Battery Tire Size	ST205/75	ST205/75	- CT20E/7E	ST205/75	- CT20E/7E	ST205/75	- CT20E/7E	ST205/75	- CT20E/7E
	C C		ST205/75		ST205/75 C		ST205/75	C C	ST205/75
Tire Load Range Tire Ply	Radial	C Radial	C Radial	C Radial	Radial	C Radial	C Radial	Radial	C Radial
Rim Size	15"	15"	Hadiai 15"	Radiai 15"	15"	Radiai 15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Brake Lights	5 0H 4.5	5 011 4.5 LED	5 011 4.5 LED	LED	5 011 4.5 LED	5 011 4.5 LED	5 011 4.5 LED	5 011 4.5 LED	5 0H 4.5 LED
Clearance/Marker Lights	LED	LED	LED	LED	LED	LED	LED	LED	LED
Trailer Plug	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way
Hallet Pluy	7-way	7-way	7-way	/-way	7-way	/-way	7-way	r-way	1-way