	.₹v	20	⁷ C47:72.72	20	20	~	20	20	.≈	~	20
	1046.1272	7C46.1472	7.7.5	1C47.1472	1C47.1672	1C47.1872	⁷ C47:20?	1CA8.1472	7C48.16.22	1CA 8.18 22	1548202
Model	22	2	25	22	22	25	2	25	25	25	25
Overall Length	15'-10"	17'-10"	16'-2"	18'-2"	20'-2"	22'-2"	24'-2"	18'-6"	20'-6"	22'-6"	24'-6"
Overall Width	92"	92"	102"	102"	102"	102"	102"	102"	102"	102"	102"
Overall Height	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"	8'-8"	8'-8"	8'-8"	8'-8"
Interior Length	12'-9"	14'-9"	12'-9"	14'-9"	16'-9"	18'-9"	20'-9"	14'-9"	16'-9"	18'-9"	20'-9"
Interior Width	69"	69"	81"	81"	81"	81"	81"	93"	93"	93"	93"
Between Wheel Wells	-	-	-	-	-	-	-	82"	82"	82"	82"
Interior Height	82"	82"	82"	82"	82"	82"	82"	82"	82"	82"	82"
Deck Height	18"	18"	18"	18"	18"	20"	20"	22"	22"	24"	24"
*Empty Weight (lbs)	1610	1650	1820	2010	2130	2250	2570	2250	2350	2670	2770
*Gross Capacity (GVWR)	7000	7000	7000	7000	7000	7000	7000	7000	7000	7000	7000
*Payload Capacity (lbs)	5390	5350	5180	4990	4870	4750	4430	4750	4650	4330	4230
Tongue Construction	3" tube	3" tube	4" tube	4" tube	4" tube	6" tube	6" tube	4" tube	4" tube	6" tube	6" tube
Tongue Length	2'-10"	2'-10"	3'-2"	3'-2"	3'-2"	3'-2"	3'-2"	3'-5"	3'-5"	3'-5"	3'-5"
Coupler	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Coupler	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame
Coupler Height	17"	17"	18"	18"	18"	18"	18"	18"	18"	18"	18"
Jack	2K swivel Formed	2K swivel Formed	2K swivel Formed	2K swivel Formed	2K swivel Formed	2K swivel Formed	2K swivel Formed	2K coupler Formed	2K coupler Formed	2K coupler Formed	2K coupler Formed
	channel	channel	channel	channel	channel	channel	channel	channel	channel	channel	channel
Crossmember Spacing	24" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Wall Uprights Spacing	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Roof Bow Spacing	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Exterior Sheeting	.024	.024	.024	.024	.024	.024	.024	.024	.024	.024	.024
Side Escape Door	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Side Escape Door Height	68"	68"	68"	68"	68"	68"	68"	68"	68"	68"	68"
Side Escape Door Width	36"	36"	36"	36"	36"	36"	36"	36"	36"	36"	36"
**Rear Door Type	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp
Rear Door Opening Height	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"
Rear Door Opening Width	66"	66"	78"	78"	78"	78"	78"	90"	90"	90"	90"
Ramp Load Capacity (lbs)	1000	1000	1000	1000	1000	1000	1000	4000	4000	4000	4000
Axles (lbs)	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500
	Drop spring	Drop spring	Drop spring	Drop spring	Drop spring	Drop spring	Drop spring	Drop spring	Drop spring	Drop spring	Drop spring
Axle Type	brake	brake	brake	brake	brake	brake	brake	brake	brake	brake	brake
Brakes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Breakaway Kit with Battery	yes CT205/75	yes cross/as	yes cross/as	yes cross/75	yes CT005/75	yes	yes cross/75	yes	yes cross/75	yes CTOOF /7F	yes CT005/75
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C	C	C	C	C	C	C
Tire Ply	Bias	Bias	Bias	Bias	Bias	Bias	Bias	Bias	Bias	Bias	Bias
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Brake Lights	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED
Clearance/Marker Lights										Incandescent	
Trailer Plug	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way